

# POWER-XTRA

Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0

NO: 900.600.503.120

## Ni-MH Battery Spec

Model: PX-80H3A2H-3.6V

Customer P/N: 900.600.503.120

Nominal Voltage: 3.6V

Capacity: 80mAh

<b>Draft</b> 起草	<b>Approved</b> 批准	<b>Customer Confirmation</b> 客户确认
Dora	Peter	

# POWER-XTRA

Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0

NO: 900.600.503.120

## Revision History

Revision	Date	Editor	Contents
A0	2018-09-10	Dora	Draft

# POWER-XTRA

Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0

NO: 900.600.503.120

## 目录

1. Preface 适用范围.....	4
2. Model 型号 .....	4
3. Appearance 表现特征 .....	4
4. Nominal specification 规格.....	4
5. Characteristics 性能 .....	5p
6. Drawing of Label 标签图.....	6
7. Dimensions 外形尺寸.....	6
8. 电池样品照片.....	6
9. Drawing Packing 包装图 .....	6
10. Cautions in use 使用须知 .....	7
11. Note 备注.....	7

# POWER-XTRA

Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0

NO: 900.600.503.120

## 1. Preface

This specification is suitable for the performance of the Power-Xtra Ni-MH rechargeable battery.

## 2. Model

PX-80H3A2H-3.6V

## 3. Appearance

There shall be no such defects as deformation, flaw, stain, discoloration or electrolyte leakage.

## 4. Nominal specification

Description		Specification	
Dimensions (Units: mm)	Diameter ( $\phi$ )	15.4 $\pm$ 0.3	
	Height (H)	19.2 $\pm$ 0.5	
	Weight/ (g)	Approx. 11g	
Nominal Voltage (V)		3.6	
Nominal capacity (mAh)		80	
Discharge Cut-off Voltage (V)		3.0	
Ambient temperature	Charge	Standard	0°C to 40°C
		Fast	10°C to 40°C
	Discharge		-10°C to 50°C
	Storage	<1 year/年	-10°C to 30°C
		<3 months/月	-10°C to 40°C
		The relative humidity should keep with in 65 $\pm$ 20%	

# POWER-XTRA

Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0

NO: 900.600.503.120

## 5. Characteristics

Unless otherwise specified, test: should be done within one month of delivery under the following conditions:

Ambient temperature : 20±5°C

Relative humidity : 65±20%

Atmospheric pressure : 960±100mbar

Test item		Condition	Specification
1. Charge	Standard	Charge at 0.1C for 16 hours	0°C to 40°C
	Fast	Charge at 0.2C for 5.25 hours	10°C to 40°C
2. Discharge		At 0.2C to 1.0V	≥100%
3. Capacity ( mAh )	Typical	Standard charge/discharge	> 80
	Minimum	Standard charge/discharge	80
4. Self-Discharge		The charged battery is stored for 28 days at 20°C±5°C. And the discharge time is measured at standard discharge	≥180minutes
5. Discharge	Standard charge 1hour rest Before Discharge by 0.2C to 1.0V		≥300minutes
	Standard charge 1hour rest Before Discharge by 1C to 0.8V		≥58minutes
6. Overcharge		0.1C charger 28 days	No leakage
7. Charge Retention		Standard charge storage:12moths Standard Discharge	Capacity retention ≥60% after 500cycle 500

8. Leakage Test		Standard charge stand for 14days		No leakage
9. High temperature test		Store at 40°C、50°C、60°C for 2 hours then charge/discharge		No leakage
10. Low temperature test		Store at 0°C for 2 hours then charge/discharge		No leakage
11. Short circuit test		Short circuit after fully charge		No explode
12. Drop test		Free fall on the concrete from 1 meters after fully charged		No leakage No short-circuit
Cycle life	Charge	Rest	Discharge	Cycles 1 to 50 shall be repeated until the discharge duration on any 50thcycle becomes Less than 3h
1	0.1C for 16h	0	0.25C for 2h20min	
2~48	0.25C for 3h10min	0	0.25C for 2h20min	
49	0.25C for 3h10min	0	0.2C to 1.0V	
50	0.1C for 16h	1~4h	0.2C to 1.0V	

# POWER-XTRA


Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0


NO: 900.600.503.120

## 6. Drawing of Label

PVC 绿色。印字方式：移印。日期按出货月份更改，YY 为年，MM 为月，年在后，月再后（年月），如 1607（2016 年 07 月），标签内容及格式如下：



## 7. Dimensions



Dimensions (Units: mm)	Diameter ( $\phi$ )	15.4 $\pm$ 0.3
	Height (H)	19.2 $\pm$ 0.5
	PVC / PVC Color	Green

## 8. 电池样品照片



## 9. Drawing Packing

整齐装泡沫托盘，内置防潮袋，每箱不超 10KG，贴侧唛；客户定制 Logo 外箱；外箱 Logo 内容格式如下：




# POWER-XTRA

Model : Power-Xtra 3.6V Ni-Mh 80 Mah with 2 Pins Button Battery

Ver:A0

NO: 900.600.503.120

PO NO.	Order 16-8	← 根据每次订单更改
MODEL NO.	900.600.503.120	
QTY	500PCS	← 根据每箱数量更改
DATE	YYYY-MM-DD	← 根据出货日期更改
Made in China		
 8 680187 001377		

## 10. Cautions in use

To ensure proper use of the battery please read the manual carefully before using it.

### 1. Handling

Do not expose to, dispose of the battery in fire.

Do not put the battery in a charger or equipment with wrong terminals connected.

Avoid shorting the battery.

Avoid excessive physical shock or vibration.

Do not disassemble or deform the battery.

Do not immerse in water.

Do not use the battery mixed with other different make, type, or model batteries.

Keep out of the reach of children.

### 2. Storage

Cycle(charge and discharge)the battery every 6-9month to maintain cell/battery performance ,When being stored for an extended period of time.

Store the battery in a cool, dry and well-ventilated area.

### 3. Disposal

Regulations vary for different countries.

Dispose of in accordance with local regulations.

## 11. Note

Any other items which are not covered in this specification shall be agreed by both parties.